



2nm 360° Red + 2nm 360° White, silver anodized

200-014G2+012G2

2nm 360° Red+2nm 360° White, silver anodized
2nm 360° Red+2nm 360° White, silver anodized

Specifications	
Number	200-014G2+012G2
Light Color	Red
Dimensions metric	Ø92,5mm x 68mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 2.7"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438019287
IP rating	IP68
Power draw (W)	2,1
UPC Code	879343019419
Connection	0.7m cable

Specifications	
Current consumption (mA @ 12VDC)	150
Stock status	Made to order
Current consumption (mA @ 24VDC)	85
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	0.82 Kg
Weight (Oz)	28.92 Oz