



2nm 180° Red, Double, silver anodized

200-016G2ST

2nm 180° Red, double, silver anodized
Vertical mounted with 0.75m cables

Specifications	
Number	200-016G2ST
Light Color	Red
Dimensions metric	See drawing
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	See drawing
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,precabled with 0.75 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438021372
IP rating	IP68
Power draw (W)	1,4
UPC Code	879343021504
Connection	0.7m cable

Specifications

**Current consumption
(mA @ 12VDC)** 145

**Current consumption
(mA @ 24VDC)** 60

Vessel size Under 12M,12-20M,20-50M

Weight (Kg) 0.54 Kg

Weight (Oz) 19.05 Oz