



2nm 180° Red, silver anodized, with 0,7m cable

200-016G2

2nm 180° Red, silver anodized
Vertical mounted with 0.75m cable

Specifications	
Number	200-016G2
Light Color	Red
Dimensions metric	104 mm x 37 mm x 45 mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>5.4cd
Dimensions imperial	4.0" x 1.4" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,precabled with 0.75 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012158
IP rating	IP68
Power draw (W)	1,5
UPC Code	879343012151
Connection	0.7m cable

Specifications

**Current consumption
(mA @ 12VDC)** 145

Stock status Usually in stock

**Current consumption
(mA @ 24VDC)** 60

Vessel size Under 12M,12-20M,20-50M

Min. feed wire gauge 0.5mm2 AWG22

Weight (Kg) 0.27 Kg

Weight (Oz) 9.49 Oz