



5nm dbl 360° white manoeuv, black anodized.

200-064ST-PRO

5nm dbl 360° white manoeuv, black anodized.

Horizontally mounted on 400-037 POM base (IP68)

Cable direction side

incl. HDPE base plate

Quality cable glands

7-13mm (9/32"- 1/2") cable diameter

Specifications	
Number	200-064ST-PRO
Light Color	White
Dimensions metric	Ø92,5mm x 124,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>52cd
Dimensions imperial	Ø3.6" x 4.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	5nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438007734
IP rating	IP68
Power draw (W)	6
UPC Code	879343007737
Connection	Plug connector
Current consumption (mA @ 12VDC)	500

Specifications	
Stock status	Made to order
Current consumption (mA @ 24VDC)	250
Vessel size	All Sizes
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	1.4 Kg
Weight (Oz)	49.38 Oz