



2nm tri-color, horizontal mount, with 0.7m cable

201-005

2nm tri-color, hor mnt, 0.7m

Horizontally mounted on HDPE base with 0,75m cable

Specifications	
Number	201-005
Light Color	Red,Green,White
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,precabled with 0.75 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438007840
IP rating	IP68
Power draw (W)	2,9
UPC Code	879343007843
Connection	0.7m cable

Specifications

**Current consumption
(mA @ 12VDC)** 213

Stock status Usually in stock

**Current consumption
(mA @ 24VDC)** 123

Vessel size 12-20M

Min. feed wire gauge 0.5mm2 AWG22

Weight (Kg) 0.52 Kg

Weight (Oz) 18.34 Oz