



3nm Masthead, silver anodized

201-011

3nm masthead, silver anodized
Vertically mounted with 0,75m cable

Specifications

| | |
|-----------------------|--|
| Number | 201-011 |
| Light Color | White |
| Dimensions metric | 74,55 x 28 x 73,16 |
| Certification | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support |
| Intensity | >15cd |
| Dimensions imperial | 2.9" x 1.1" x 2.88" |
| Approved to | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR |
| Visibility | 3nm |
| Included In Package | 1 Navigation light,precabled with 0.75 meter shielded marine grade cable,2 Mounting screws (M6 * 8 mm),Installation guide |
| Operating temperature | -25°C to 55°C |
| Mounting | Vertical |
| Materials | Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane |
| Operating Voltage | 10-32VDC |
| EAN | 5704438009707 |
| IP rating | IP68 |
| Power draw (W) | 3 |
| UPC Code | 879343009700 |
| Connection | 0.7m cable |

Specifications

**Current consumption
(mA @ 12VDC)** 232

Stock status Usually in stock

**Current consumption
(mA @ 24VDC)** 127

Vessel size 12-20M

Min. feed wire gauge 0.5mm2 AWG22

Weight (Kg) 0.43 Kg

Weight (Oz) 15.17 Oz