



2nm yellow Towing, black anodized

201-013-B

2nm amber towing, black anodized
Horizontally mounted with 2,5m cable

Specifications	
Number	201-013-B
Light Color	Yellow
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,precabled with 2.5 meter shielded marine grade cable,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010239
IP rating	IP68
Power draw (W)	1,7
UPC Code	879343010232
Connection	2.5m cable

Specifications

Current consumption (mA @ 12VDC) 124

Stock status Usually in stock

Current consumption (mA @ 24VDC) 71

Vessel size Under 12M,12-20M,20-50M

Min. feed wire gauge 0.5mm2 AWG22

Weight (Kg) 1.01 Kg

Weight (Oz) 35.62 Oz