



3nm Masthead/360° White, black anod. - Powerboat

201-021-B

3nm masthead/360° white, black anodized
Horizontal mounted with 0,75m cable

Specifications	
Number	201-021-B
Light Color	White
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>15cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light,precabled with 0.75 meter shielded marine grade cable,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438009974
IP rating	IP68
Power draw (W)	3,6
UPC Code	879343009977
Connection	0.7m cable

Specifications

**Current consumption
(mA @ 12VDC)** 300

Stock status Usually in stock

**Current consumption
(mA @ 24VDC)** 148

Vessel size 12-20M

Min. feed wire gauge 0.5mm2 AWG22

Weight (Kg) 0.54 Kg

Weight (Oz) 19.05 Oz