



## 5nm Masthead, black anodized

300-037-B

5 nm Masthead (blk), vert CB mnt, 0.7m  
Vertically mounted with 0,75m cable.

Specifications	
Number	300-037-B
Light Color	White
Dimensions metric	107 x 92,5 x 74
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under Support
Intensity	>52cd
Dimensions imperial	4.2" x 3.6" x 2.9"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	5nm
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438003330
IP rating	IP68
Power draw (W)	7
UPC Code	879343003333
Connection	0.7m cable
Current consumption (mA @ 12VDC)	0

**Specifications**

<b>Stock status</b>	Made to order
---------------------	---------------

<b>Current consumption (mA @ 24VDC)</b>	290
---	-----

<b>Vessel size</b>	20-50M
--------------------	--------

<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
-----------------------------	--------------------------

<b>Weight (Kg)</b>	1.06 Kg
--------------------	---------

<b>Weight (Oz)</b>	37.39 Oz
--------------------	----------