



3nm 360° Red w/ Windex mount & light

300-114G2W

3nm 360° Red with windex mount & light
Horizontally mounted on (400-034)
Cable side / cable down base.

Specifications

| | |
|----------------------------------|--|
| Number | 300-114G2W |
| Light Color | Red,White |
| Dimensions metric | Ø92,5mm x 92,5mm |
| Certification | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support |
| Intensity | >15cd |
| Dimensions imperial | Ø3.6" x 3.6" |
| Approved to | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR |
| Visibility | 3nm |
| Operating temperature | -25°C to 55°C |
| Mounting | Horizontal |
| Materials | Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane |
| Operating Voltage | 10-32VDC |
| EAN | 5704438013933 |
| IP rating | IP68 |
| Power draw (W) | 2,9 |
| UPC Code | 879343013936 |
| Connection | Plug connector |
| Current consumption (mA @ 12VDC) | 210 |

Specifications

| | |
|--------------|---------------|
| Stock status | Made to order |
|--------------|---------------|

| | |
|-------------------------------------|-----|
| Current consumption (mA @ 24VDC) | 120 |
|-------------------------------------|-----|

| | |
|-------------|----------|
| Vessel size | Over 50M |
|-------------|----------|

| | |
|----------------------|--------------|
| Min. feed wire gauge | 0.5mm2 AWG22 |
|----------------------|--------------|

| | |
|-------------|---------|
| Weight (Kg) | 1.17 Kg |
|-------------|---------|

| | |
|-------------|----------|
| Weight (Oz) | 41.27 Oz |
|-------------|----------|