



## 2nm dbl port, silver anodized

301-002ST

This LED Navigation light comes in black and silver, with the best technology available and impressive robustness. It is easy to install. Below is a list of more great features. For more detailed information, please download technical files.

- For Boats and Yachts up to 50m (164 ft)
- High quality materials used for long life.
- Water and vibration proof.
- No EMC noise on your AIS/VHF.
- Multivoltage - 12 to 24 Volt.
- Worldwide approvals.
- Including potted-in power cable for ultimate waterproofness.
- 5 year warranty.

Vertically mounted with 2,5m cables

### Specifications

Number	301-002ST
Light Color	Red
Dimensions metric	100 x 100 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under Support
Intensity	>5.4cd
Dimensions imperial	3.9" x 3.9" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,precabled with 2.5 meter shielded marine grade cable,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010383
IP rating	IP68
Power draw (W)	1,2
UPC Code	879343010386
Connection	2.5m cable

## Specifications

**Current consumption  
(mA @ 12VDC)** 90

**Stock status** Not usually in stock

**Lead time** 2-3 weeks

**Current consumption  
(mA @ 24VDC)** 50

**Vessel size** Under 12M,12-20M,20-50M

**Min. feed wire gauge** 0.5mm2 AWG22

**Weight (Kg)** 1 Kg

**Weight (Oz)** 35.27 Oz