



2nm Port, silver anodized

301-009

This LED Navigation light comes in black and silver, with the best technology available and impressive robustness. It is easy to install. Below is a list of more great features. For more detailed information, please download technical files.

- For Boats and Yachts up to 50m (164 ft)
- High quality materials used for long life.
- Water and vibration proof.
- No EMC noise on your AIS/VHF.
- Multivoltage - 12 to 24 Volt.
- Worldwide approvals.
- Including potted-in power cable for ultimate waterproofness.
- 5 year warranty

Horizontal mounted with 2,5m cable

Specifications	
Number	301-009
Light Color	Red
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopelight.com under Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,precabled with 2.5 meter shielded marine grade cable,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012981
IP rating	IP68
Power draw (W)	1,2
UPC Code	879343012984
Connection	2.5m cable

Specifications

**Current consumption
(mA @ 12VDC)** 90

Stock status Usually in stock

Lead time 1-2 weeks

**Current consumption
(mA @ 24VDC)** 50

Vessel size Under 12M,12-20M,20-50M

Min. feed wire gauge 0.5mm2 AWG22

Weight (Kg) 0.64 Kg

Weight (Oz) 22.57 Oz