



3nm port, black anodized

301-102-B

3nm port, black anodized
Vertical mounted with 2.5m cable

Specifications

Number	301-102-B
Light Color	Red
Dimensions metric	92,5 x 28 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>15cd
Dimensions imperial	3.6" x 1.1" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light,precabled with 2.5 meter shielded marine grade cable,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010574
IP rating	IP68
Power draw (W)	2
UPC Code	879343010577
Connection	2.5m cable

Specifications

**Current consumption
(mA @ 12VDC)** 150

Stock status Usually in stock

**Current consumption
(mA @ 24VDC)** 100

Vessel size Over 50M

Min. feed wire gauge 0.5mm2 AWG22

Weight (Kg) 0.39 Kg

Weight (Oz) 13.76 Oz