



## 3nm dbl stern , silver anodized

301-105ST-CD

3nm dbl stern , silver anodized

Horizontal mounted on (400-035) CD base.

### Specifications

Number	301-105ST-CD
Light Color	White
Dimensions metric	Ø92,5mm x 96,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under Support
Intensity	>15cd
Dimensions imperial	Ø3.6" x 3.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438014503
IP rating	IP68
Power draw (W)	1,7
UPC Code	879343014506
Connection	Plug connector
Current consumption (mA @ 12VDC)	130

## Specifications

**Stock status** Usually in stock

**Current consumption  
(mA @ 24VDC)** 72

**Vessel size** Over 50M

**Min. feed wire gauge** 0.5mm2 AWG22

**Weight (Kg)** 1 Kg

**Weight (Oz)** 35.27 Oz