



3nm 135° stern, silver anodized, horizontal mount, with plug connector

301-105

3nm stern, hor mnt

Horizontally mounted on alu base & PE base plate

Cable direction side or bottom

Specifications	
Number	301-105
Light Color	White
Dimensions metric	Ø92,5mm x 74,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>15cd
Dimensions imperial	Ø3.6" x 2.9"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438009462
IP rating	IP68
Power draw (W)	1,7
UPC Code	879343009465
Connection	Plug connector

Specifications

**Current consumption
(mA @ 12VDC)** 130

Stock status Usually in stock

**Current consumption
(mA @ 24VDC)** 72

Vessel size Over 50M

Min. feed wire gauge 0.5mm2 AWG22

Weight (Kg) 0.99 Kg

Weight (Oz) 34.92 Oz